StarLink Charger 2.0



StarLink Charger 2.0

StarLink Custom Charger 2.0

Unique StarLink 2.0 chargers for mRIC R, RIC RT, and custom hearing aids. All StarLink 2.0 chargers have on-board turbo charging functionality.

StarLink Charger 2.0

TECHNICAL DATA

	StarLink Charger 2.0	StarLink Premium Charger 2.0
Dimensions	92mm x 63mm x 56mm [3.6" x 2.5" x 2.2"]	92mm x 63mm x 56mm [3.6" x 2.5" x 2.2"]
Weight	117 grams [4.1 ounces]	Standard: 117 grams [4.1 ounces] Custom: 110 grams [3.9 ounces]
Battery Capacity	None	Standard: 650 mAh Custom: 350 mAh
On-board Battery Charge Time	N/A	Standard: 3.5 hours Custom: 2.25 hours
Power Supply Plug	USB-C	USB-C
Power Supply	Power through USB-C required	Built-in, lithium-ion rechargeable
Cord-free Charging	None	After initial charge, a pair of hearing aids can be fully charged three times before the charger needs to be connected to power source (e.g., a wall outlet)
Color	Black	Black
Hearing Aid LEDs	White (n=2)	White (n=2)
On-board Battery LEDs	N/A	White (n=4)
Operating Temperature	10°C (50°F) to 40°C (104°F)	10°C (50°F) to 40°C (104°F)
Storage & Transportation Temperature	-10°C (14°F) to 45°C (113°F)	-10°C (14°F) to 45°C (113°F)
Operating Humidity	10% rH to 95% rH	10% rH to 95% rH

StarLink

The Starkey logo and StarLink are trademarks of Starkey Laboratories, Inc.
©2023 Starkey Laboratories, Inc. All Rights Reserved. 10/23 SPEC3075-00-EN-XX